

[PK503 series]

피삭재		합금강, 고탄소강				프리하든강, 공구강 HRc30 ~ 40			
(V)m/min		130 ~ 150				100 ~ 120			
외경(mm)	(r.p.m.)	fz			(r.p.m.)	fz			
		Slot	Side Cutting	Slot		Slot	Side Cutting	Slot	
6	7,400	0.030	0.045	0.018	5,800	0.025	0.030	0.012	
8	5,600	0.035	0.062	0.025	4,400	0.030	0.045	0.018	
10	4,600	0.045	0.075	0.030	3,500	0.040	0.048	0.019	
12	3,700	0.050	0.087	0.035	3,000	0.045	0.052	0.020	
14	3,200	0.055	0.090	0.036	2,500	0.053	0.056	0.022	
16	2,800	0.055	0.090	0.036	2,200	0.060	0.060	0.024	
20	2,200	0.080	0.095	0.038	1,800	0.066	0.066	0.026	
	ap		1.0D	1.0D	0.5D		1.0D	1.0D	0.5D
	ae		1.0D	0.5D	1.0D		1.0D	0.3D	1.0D

피삭재		SUS304 · 316 · 프리하든강 HRc40 ~ 45				티타늄합금			
(V)m/min		50 ~ 70				30 ~ 50			
외경(mm)	(r.p.m.)	fz			(r.p.m.)	fz			
		Slot	Side Cutting	Slot		Slot	Side Cutting	Slot	
6	3,200	0.020	0.030	0.012	2,100	0.017	0.020	0.008	
8	2,400	0.030	0.040	0.016	1,600	0.025	0.025	0.010	
10	1,900	0.040	0.055	0.022	1,300	0.035	0.040	0.016	
12	1,600	0.045	0.065	0.026	1,100	0.040	0.050	0.020	
14	1,360	0.048	0.070	0.028	900	0.043	0.053	0.021	
16	1,200	0.050	0.075	0.030	800	0.045	0.055	0.022	
20	1,000	0.052	0.083	0.033	600	0.050	0.057	0.023	
	ap		0.5D	1.0D	0.5D		0.5D	1.0D	0.5D
	ae		1.0D	0.5D	1.0D		1.0D	0.3D	1.0D

