


[ZS1(2)04, ZS204 series] ▶ 측면 절삭 가공

피삭재 경도	열처리강									
	HRc40 ~ HRc50		HRc50 ~ HRc55		HRc55 ~ HRc60		HRc60 ~ HRc65		HRc65 ~ HRc70	
외경(mm)	RPM	FEED	RPM	FEED	RPM	FEED	RPM	FEED	RPM	FEED
4	17,200	1,690	11,440	1,140	9,360	700	7,280	430	6,170	310
6	13,450	1,820	8,970	1,230	6,890	720	5,460	450	4,810	330
8	9,100	1,750	6,760	1,170	5,200	670	4,160	420	3,640	310
10	8,000	1,630	5,330	1,090	4,160	620	3,320	400	2,860	280
12	6,830	1,630	4,550	1,010	3,450	580	2,730	370	2,420	260

RPM = rev. / min.
FEED = mm / min.



[ZSPM4... series]

피삭재 경도	열처리강									
	~HRc40		HRc40 ~ HRc50		HRc50 ~ HRc55		HRc55 ~ HRc60		HRc60 ~ HRc65	
D X R(mm)	RPM	FEED	RPM	FEED	RPM	FEED	RPM	FEED	RPM	FEED
3 X R0.5	9,550	6,500	6,900	4,150	4,550	2,750	2,850	1,150	1,900	610
4 X R0.5	7,950	7,000	5,750	4,600	4,000	3,200	2,550	1,350	1,750	700
6 X R0.5	5,800	7,650	4,100	4,900	2,900	3,500	1,850	1,850	1,350	795
6 X R1.0	5,800	7,650	4,100	4,900	2,900	3,500	1,850	1,850	1,350	795
8 X R1.0	4,350	7,650	3,050	4,900	2,200	3,500	1,400	1,850	995	795
8 X R2.0	4,350	7,650	3,050	4,900	2,200	3,500	1,400	1,850	995	795
10 X R1.0	3,500	7,650	2,450	4,900	1,750	3,500	1,100	1,850	795	795
10 X R2.0	3,500	7,650	2,450	4,900	1,750	3,500	1,100	1,850	795	795
12 X R2.0	2,900	7,650	2,050	4,900	1,450	3,500	925	1,850	665	795
12 X R3.0	2,900	7,650	2,050	4,900	1,450	3,500	925	1,850	665	795

RPM = rev. / min.
FEED = mm / min.

